

Technical Spec Sheet

SG56 PUNCHED ALUMINIUM ROLLING GRILLE

Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: sales@simflex.co.uk
Website: www.simflex.co.uk

Curtain construction and Weight

56mm x 13.5mm single walled punched extruded aluminium lath.
Punched holes are 80mm x 30mm, offering approximately 47% visibility.
Reinforcing lath (30mm x 13.5mm) for use on shutters over 3000mm wide
Weight 6.2kg m².

Bottom Bar and Guides

The bottom bar is 60mm x 13.5mm twin walled extruded aluminium with
bottom rubber for a manual shutter and 50mm x 13mm twin walled extruded
aluminium with bottom rubber for a motorised shutter.
Guides for a 180mm & 205mm box are 66mm x 27mm Extruded Aluminium
construction including brush strips.
Guides for 250mm box are 75mm x 27mm Extruded Aluminium construction
including brush strips.

Shutter Hood

Die cast aluminium end plates with a preformed 2-piece aluminium hood.
Shutter hood ranges from 180mm to 250mm, subject to size of the shutter.

Operation and Locking

Manual spring and lock operation with unique bottom lock for manual doors.
Motorised with tubular 220/240 volt single-phase motor with control options
including keyswitch, rocker switch, push button or remote radio control with a
hand-held transmitter, manual wind and brake.

Finishes/ Colour

Polyester powder-coated (PPC) to White RAL 9016 or Brown RAL 8019 as
standard or to any stocked BS or RAL colour at additional cost.

Applications

Medium level of security for shop fronts, serveries and bars where vision is
required. Ideal for larger widths.

SG56 Punched Aluminium

