Technical Spec Sheet

'CONCEPT 33' SLIDING / FOLDING GRILLE

Curtain construction

The top and bottom of each panel section is fitted with a 102mm high aluminium panel. This panel consists of an aluminium extrusion 2mm thick. It is connected into extruded hinge cleats with a 15° off set to facilitate folding. The curtain is constructed from 12mm aluminium tubes centred on a solid core which are connected across their span via 75mm decorative plates. The checker plate pattern is created by alternating the plates and spaces. PLEASE NOTE – these are open grilles and can be accessible by arm/hands.

Overhead track

Manufactured from a strong tempered aluminium alloy class 6351 –T6 Extrusion, 34mm wide x 42mm total height.

Locking

Lock members are integral 50mm x 32mm standard extruded aluminium hollow posts. They are at both ends of each grille, at intervals of 2500mm maximum on full height doors and at 1500mm spacing (approx) on counter tops. Additional posts to support curves as necessary. Lead posts incorporate Adams Rite mortice locks operated by 5-pin cylinders on each side. Intermediate posts incorporate drop bolts locating into flush floor sockets. Drop bolts can be deadlocked with 5 pin cylinders.

Finishes

Natural anodised or white, black, light or medium bronze powder coat paint

Weight

'Concept 33' - Approx 8kgs/m²

Warranty

All our products carry a minimum 1 year warranty from date of installation. The only exceptions are misuse, abuse or vandalism.



Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street, Ampthill, Bedfordshire, MK45 2HP

> Telephone number: 01525 841100 Registration No. 2347541

> > Email: sales@simflex.co.uk Website: www.simflex.co.uk

Concept 33





