

Technical Spec Sheet

SG89 SOLID ALUMINIUM ROLLER SHUTTER

Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: sales@simflex.co.uk
Website: www.simflex.co.uk

Curtain construction and Weight

89mm x 19mm single walled solid extruded aluminium lath.
Weight 8kg m².

Bottom Bar and Guides

The bottom bar is 89mm x 19mm twin walled extruded aluminium with bottom rubber.

Guides are 65mm x 38mm or 75mm x 38mm Extruded Aluminium construction including brush strips.

Electric shutters require 50mm x 50mm steel box section (both sides) used to allow for motor unit and safety brake. A 76mm x 50mm box section will be used for shutters over 160kg in weight.

Shutter Hood

Steel end plates with a preformed 2-piece aluminium hood. Shutter hood ranges from 250mm to 365mm subject to the size of the shutter.

Operation and Locking

Manual spring and lock operation with unique bottom lock for manual doors.

Motorised with tubular 220/240 volt single-phase motor with control options including keyswitch, rocker switch, push button or remote radio control with a hand-held transmitter, manual wind and brake

Finishes/ Colour

Mill finished or silver anodised, plus polyester powder-coated (PPC) to any stocked BS or RAL colour at additional cost.

Applications

High security for commercial or industrial applications.

SG89 Solid Aluminium

