

Technical Spec Sheet

SG77GD SOLID ALUMINIUM GARAGE DOOR ROLLER SHUTTER

Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: sales@simflex.co.uk
Website: www.simflex.co.uk

Curtain construction and Weight

77mm x 19mm foam filled insulated double skinned aluminium roll formed lath.
Weight 7.1kg/m²

Bottom Bar and Guides

The bottom bar is 77mm x 19mm twin walled extruded aluminium with bottom rubber.

Guides are either 75mm or 90mm x 35mm (subject to shutter size) including 2 brush strips to seal against the lath. Guides are supplied in White or Brown and can be powder coated to colour match the curtain at an additional cost.

Shutter Hood

Die cast aluminium end plates, that locate into the side guides, with 2 piece roll formed aluminium casing. For heavier doors the end plates will be zinc plated steel for additional strength. Shutter hood ranges from 300mm to 360mm subject to the size of the shutter.

Operation and Locking

Garage doors are supplied with the Ansa remote control unit as standard, to include photocell, 2 hand transmitters, a courtesy light and manual override.

Finishes/ Colour

Curtain is polyester powder-coated (PPC) to the following; White RAL 9016, Brown RAL 8019, Green RAL 6005, Black RAL 9005, Red RAL 3004, Blue RAL 5011, Sliver RAL 9006 and Cream BS08817 as standard. Rosewood or Golden Oak wood effect or to any stocked BS or RAL colour at additional cost.

Guides are polyester powder-coated (PPC) to White RAL 9016 or Brown RAL 8019 as standard and can be powder coated to colour match the curtain at an additional cost.

Applications

High security for domestic applications.

SG77GD Solid Aluminium

