

# Technical Spec Sheet

## SG75 PUNCHED STEEL ROLLING GRILLE

### Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,  
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: [sales@simflex.co.uk](mailto:sales@simflex.co.uk)  
Website: [www.simflex.co.uk](http://www.simflex.co.uk)

### Curtain construction and Weight

75mm x 17mm interlocking 20 gauge convex steel lath with either 47mm x 76mm or 25mm x 150mm punched holes.  
Weight 11kg m<sup>2</sup>.

### Bottom Bar and Guides

The bottom bar consists of a mild steel 75mm x 51mm 'T' Bar or 31 x 68mm 'L' section. Guides are 65mm x 32mm x 3mm prefixed to 40mm x 40mm x 3mm unistrut for ease of installation (subject to shutter size)

### Shutter Hood

Galvanised steel end plates with locating lugs for strength and safety with preformed 2-piece aluminium hood.  
Shutter hood ranges from 250mm to 360mm, subject to size of the shutter.

### Operation and Locking

Manual spring and lock operation, spring balanced barrel with either bottom bar lock or guide rail bullet locks.

Motorised with tubular 220/240 volt single-phase motor with control options including keyswitch, rocker switch, push button or remote radio control with a hand-held transmitter, manual wind and brake.

### Finishes/ Colour

Galvanised as standard.  
Polyester powder-coated (PPC) to any stocked BS or RAL colour or to any other non-standard colour at additional cost.

### Applications

Medium to high security office, commercial and industrial applications.  
Especially suitable where superior aesthetics are required due to unique guide section and continental style hood.

### SG75 Punched Steel

