

# Technical Spec Sheet

## SG77 SOLID ALUMINIUM ROLLER SHUTTER

### Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,  
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: [sales@simflex.co.uk](mailto:sales@simflex.co.uk)  
Website: [www.simflex.co.uk](http://www.simflex.co.uk)

### Curtain construction and Weight

77mm x 19mm single walled solid extruded aluminium lath.  
Weight 10.05kg m<sup>2</sup>.

### Bottom Bar and Guides

The bottom bar is 77mm x 19mm twin walled extruded aluminium with bottom rubber.

Guides are 90mm x 35mm Extruded Aluminium construction including brush strips.

### Shutter Hood

Die cast aluminium end plates with a preformed 2-piece aluminium hood.  
Shutter hood ranges from 250mm to 360mm subject to the size of the shutter.

### Operation and Locking

Manual spring and lock operation with unique bottom lock for manual doors.  
Motorised with tubular 220/240 volt single-phase motor with control options including keyswitch, rocker switch, push button or remote radio control with a hand-held transmitter, manual wind and brake.

### Finishes/ Colour

Polyester powder-coated (PPC) to White RAL 9016 or Brown RAL 8019 as standard or to any stocked BS or RAL colour at additional cost.

### Applications

Medium security for shop fronts, serveries and bars.

### SG77 Solid Aluminium

