

Technical Spec Sheet

SG84 SOLID ALUMINIUM ROLLER SHUTTER

Curtain construction and Weight

84mm x 19mm single walled solid extruded aluminium lath.
Weight 8kg m².

Bottom Bar and Guides

The bottom bar is 88mm x 19mm twin walled extruded aluminium with bottom rubber.
Guides are 90mm x 35mm Extruded Aluminium construction including brush strips.

Shutter Hood

Die cast aluminium end plates with a preformed 2-piece aluminium hood.
Shutter hood ranges from 250mm to 300mm subject to the size of the shutter.

Operation and Locking

Manual spring and lock operation with unique bottom lock for manual doors.
Motorised with tubular 220/240 volt single-phase motor with control options including keyswitch, rocker switch, push button or remote radio control with a hand-held transmitter, manual wind and brake.

Finishes/ Colour

Polyester powder-coated (PPC) to White RAL 9016 or Brown RAL 8019 as standard or to any stocked BS or RAL colour at additional cost.

Applications

Medium to high level of security for retail and commercial premises. Ideal for larger widths.
Suitable for internal or external use.

Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: sales@simflex.co.uk
Website: www.simflex.co.uk

SG84 Solid Aluminium

