

Technical Spec Sheet

SGT&L TUBE & LINK ALUMINIUM ROLLING GRILLE

Curtain construction and Weight

Brickbond pattern slots creating windows of approximately 260mm x 45mm or
Inline pattern slots creating windows of approximately 110mm x 76mm.
Weight 10.5kg m².

Bottom Bar & Guides

The bottom bar consists of a mild steel 75mm x 51mm 'T' Bar or 31mm x 68mm
'L' section.

Guides are 50mm/ 65mm/ 75mm x 32mm x 3mm dependant on width.
Electric shutters require 50mm x 50mm steel box section (both sides) used to
allow for motor unit and safety brake. A 76mm x 50mm box section will be used
for shutters over 160kg in weight.

Shutter Hood

Steel end plates with a preformed 2-piece aluminium hood.
Shutter hood ranges from 250mm to 365mm subject to the size of the shutter.

Operation & Locking

Manual spring and lock operation with unique bottom lock for manual doors.
Motorised with tubular 220/240 volt single-phase motor with control options
including keyswitch, rocker switch, push button or remote radio control with a
hand-held transmitter, manual wind and brake

Finishes/ Colour

Mill finished aluminium tube and links.
Silver anodised or polyester powder coated (PPC) to any stocked BS or RAL
colour at additional cost.

Applications

Low security for shop fronts, serveries and bars.

Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: sales@simflex.co.uk
Website: www.simflex.co.uk

SGT&L Tube & Link Aluminium

