

Technical Spec Sheet

SG44 SOLID ALUMINIUM ROLLER SHUTTER

Manufacturer details

SimFlex Grilles and Closures Ltd, 9 Woburn Street,
Amphill, Bedfordshire, MK45 2HP

Telephone number: 01525 841100

Email: sales@simflex.co.uk
Website: www.simflex.co.uk

Curtain construction and Weight

44mm x 9mm twin walled solid extruded aluminium lath.
Weight 8kg m².

Bottom Bar and Guides

The bottom bar is 50mm x 8mm extruded aluminium with reinforcing angle or bottom rubber.
Guides are 60mm x 22mm Extruded Aluminium construction including brush strips.

Shutter Hood

Die cast aluminium end plates with a preformed 2-piece aluminium hood.
Shutter hood ranges from 165mm to 250mm, subject to size of the shutter.

Operation and Locking

Manual spring and lock operation with unique bottom lock for manual doors.
Motorised with tubular 220/240 volt single-phase motor with control options including keyswitch, rocker switch, push button or remote radio control with a hand-held transmitter, manual wind and brake.

Finishes/ Colour

Polyester powder-coated (PPC) to White RAL 9016 or Brown RAL 8019 as standard or to any stocked BS or RAL colour at additional cost.

Applications

Medium to high level of security for domestic, retail and commercial premises.
Suitable for internal or external use.

SG44 Solid Aluminium

